

RoHS Compliant






P.C.B LAND PATTERN


SS-B50x-x-S246


MODEL	X(mm)
SS-B50	2.0
SS-B50A	3.0
SS-B50C	4.0

SLIDER COLOR :

Black : B
White : W







CIRCUIT DIAGRAM

SPECIFICATIONS

Rating	0.3A 6V DC
Insulation Resistance	50MΩ Min.
Dielectric Withstanding Voltage	AC 250 V(50Hz)1min
Contact Resistance	100mΩ Max.
Operating Force	200 ± 50gf
Operating Life	10,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
E	TERMINAL	6	PHOSPHOR BRONZE	Ag plated
D	CLIP	2	BECU	Ag plated
C	COVER	1	SUS	
B	CASE	1	PA6T	Black
A	SLIDER	1	PA46	Black

ITEM NO.	DESCRIPTION	DRAWN	DATE
4	更新圖面	Jack	121018
3	更新材質	Jack	061015
2	更新高度代碼	Jack	060515
1	新增高度選項	Jack	032514

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 12/10/18	MAT'L	
CHECKED BY: Jacky Chen	DATE 12/10/18	FINISH	
APPROVED BY: Tony Kao	DATE 12/10/18	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	SWITCH		
MODLE	SLIDE SWICTH		
DWG NO.	SS-B50x-x-S246	SIZE	A4
PART NO.	SS-B50x-x-S246	VER	R4