





RoHS Compliant

## PRODUCT IMAGE



## SCHEMATIC




| Model No. | Switcning Position | | |
|---|---|---|---|
| T101 | ON | NONE | ON |
| T102 | ON | NONE | (ON) |
| T103 | ON | OFF | ON |
| T104 | (ON) | OFF | (ON) |
| T105 | ON | OFF | (ON) |
| Term Comm. | 2-3 | OPEN | 2-1 |

## SPECIFICATIONS:

CONTACT RATING : 5 AMPS / 120V AC or 28V DC
2 AMPS / 250V AC or 0.4VA AMPS @ 20V ACor DC
20VELECTRICAL LIFE : 50,000 make-and-break cycles at full load.
CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 VDC
100 mA , for both coin silver and gold plated contacts.
INSULATION RESISTANCE : 1,000 MΩ min
DIELETRIC STRENGTH : 1,000 V RMS @ sea level.
OPERATING TEMPERTURE : -30˚C to 130˚C

## MTAERIALS:

CASE : Dially phthalate (DAP)(UL-94V-0)
ACTUATOR : Brass,chrome plated.
BUSHING : Brass. nickel plated.
HOUSING : Stainless steel.
TERMINAL/CONTACT : Brass , witch silver or gold plated.
or gold over silver
SWITCH SUPPORT : Brass , tin plated.

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|---|---|---|---|
| 1 | 圖面料號、標註尺寸更新 | FrankWu | 010312 |

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3˚
3RD. ANGEL'S
UNITS MM

| | | DATE |
|---|---|---|
| DRAWN BY: | Frank Wu | 01/03/12 |
| CHECKED BY: | Jacky Chen | 01/03/12 |
| APPROVED BY: | Tony Kao | 01/03/12 |

| | | | |
|---|---|---|---|
| MAT'L | | TITLE | SWITCH |
| FINISH | | MODLE | TOGGLE ROCKER SWITCH |
| SCALE | 1 : 1 | DWG NO. | T10xT1B4A1 |
| SHEET NO. | 1 of 1 | PART NO. | T10xT1B4A1 |

SIZE A4 VER B