



MODEL NO.	DC-060D-x-S187
SCHEMATIC	
CENTER PIN	φ1.0 mm
	φ1.3 mm

- SPECIFICATION**
- Rating : DC 16V 2.0A
 - Contact resistance : ≤ 50mΩ
 - Insulation resistance : ≥ 100MΩ
 - Withstand voltage : 500VAC
 - Insertion and extraction force : 3-30N
 - life test : 5,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
④	HOUSING	1	PA9T(Black)	
③	TERMINAL#3	1	PHOSPHOR BRONZE	Ag-Plating
②	TERMINAL#2	1	PHOSPHOR BRONZE	Ag-Plating
①	TERMINAL#1	1	BRASS	Ag-Plating

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新為A0版	Jack	021317
1	新增SPEC	Jack	110215

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	02/13/17		MODLE	DC JACK
CHECKED BY:	DATE	SCALE	DWG NO.	DC-060D-x-S187
Jacky Chen	02/13/17	1 : 1	PART NO.	DC-060D-x-S187
APPROVED BY:	DATE	SHEET NO.	SIZE	A4
Tony Kao	02/13/17	1 of 1	VER	A0