


SPECIFICATION

1. Rating : DC 30V 0.5A
2. Contact resistance : $\leq 50m\Omega$ Max
3. Insulation resistance : $\geq 100M\Omega$ Min
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

SCHEMATIC

DC-067DS-1.0



P.C.B LAYOUT TOP VIEW

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
5	CONTACT FOOT	1	BRASS	Ag-Plating
4	PIN	1	BRASS	Ag-Plating
3	SPRING	1	SUS301	Ag-Plating
2	CURVE PIECE	1	BRASS	Ag-Plating
1	HOUSING	1	LCP	

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	12/09/14			
CHECKED BY:	DATE	FINISH	MODLE	DC JACK
Jacky Chen	12/09/14			
APPROVED BY:	DATE	SCALE	DWG NO.	DC-067DS-1.0-HF-S125
Tony Kao	12/09/14	1 : 1	PART NO.	DC-067DS-1.0-HF-S125
		SHEET NO.	1 of 1	
				SIZE A4
				VER R

ITEM NO.	DESCRIPTION	DRAWN	DATE