



PLUG SPEC

NOTES:

1. ELECTRICAL CHARACTERISTICS:

1-1 CONTACT RESISTANCE: 50mΩ MAX. (INITIAL)
100mΩ MAX. (FINAL)

1-2. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.

1-3. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500V DC

2. MECHANICAL CHARACTERISTICS:

2-1. PLUG INSERTION FORCE : 0.3~3.0KGS .

2-2. PLUG WITHDRAWAL FORCE : 0.3~3.0KGS .

3. DURABILITY TEST: 5,000 CYCLES .

Model No.	PJ-3917D-S214
Schematic code	

ITEM	DESCRIPTIONs	MATERIAL	FINISH	Q'TY
⑤	MYLAR			1
④	CONTACT 3	PHOSPHOR BRONZE	GOLD FLASH	1
③	CONTACT 2	PHOSPHOR BRONZE	GOLD FLASH	2
②	CONTACT 1	PHOSPHOR BRONZE	GOLD FLASH	4
①	HOUSING	PA9T	BLACK	1

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	09/14/16			
CHECKED BY:	DATE	FINISH	MODLE	PHONE JACK
Jacky Chen	09/14/16			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-3917D-S214
Tony Kao	09/14/16	1 : 1	PART NO.	PJ-3917D-S214
		SHEET NO.	1 of 1	
				SIZE A4
				VER R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新料號	Jack	091416
1	新增電路選項	Jack	031016