



NOTES:

1. ELECTRICAL CHARACTERISTICS:

1-1 CONTACT RESISTANCE: 50mΩ MAX. (INITIAL)
100mΩ MAX. (FINAL)

1-2. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE.

1-3. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500V DC

2. MECHANICAL CHARACTERISTICS:

2-1. PLUG INSERTION FORCE : 0.3~3.0KGS .

2-2. PLUG WITHDRAWAL FORCE : 0.3~3.0KGS .

3. DURABILITY TEST: 5,000 CYCLES .

| | |
|----------------|---------------|
| Model No. | PJ-3917D-S214 |
| Schematic code | |

| ITEM | DESCRIPTIONs | MATERIAL | FINISH | Q'TY |
|------|--------------|-----------------|------------|------|
| ⑤ | MYLAR | | | 1 |
| ④ | CONTACT 3 | PHOSPHOR BRONZE | GOLD FLASH | 1 |
| ③ | CONTACT 2 | PHOSPHOR BRONZE | GOLD FLASH | 2 |
| ② | CONTACT 1 | PHOSPHOR BRONZE | GOLD FLASH | 4 |
| ① | HOUSING | PA9T | BLACK | 1 |

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

| | | | | |
|--------------|----------|-----------|----------|---------------|
| DRAWN BY: | DATE | MAT'L | TITLE | JACK |
| Jack Lu | 09/14/16 | | | |
| CHECKED BY: | DATE | FINISH | MODLE | PHONE JACK |
| Jacky Chen | 09/14/16 | | | |
| APPROVED BY: | DATE | SCALE | DWG NO. | PJ-3917D-S214 |
| Tony Kao | 09/14/16 | 1 : 1 | PART NO. | PJ-3917D-S214 |
| | | SHEET NO. | 1 of 1 | |
| | | | SIZE | A4 |
| | | | VER | R2 |

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|----------|-------------|-------|--------|
| 2 | 更新料號 | Jack | 091416 |
| 1 | 新增電路選項 | Jack | 031016 |