


MUSB-5B-VD-x-S175


鍍層厚度 :

Blank : 1u"
2 : 15u"
3 : 30u"










P.C.B LAYOUT MOUNTING PATTERN



SPECIFICATIONS

Electrical :

1.Current Rating : 1.0A / contact terminal
2.Voltage Rating : 30V DC
3.Contact Resistance : 50 mΩ Max
4.Dielectric Withstanding Voltage :
300 V AC AT Sec Level
5.Insulation Resistance : 100 MΩ Min

Mechanical :

1.Connector Mate and Unmate Force
Mate force : 3.0 kgf (Max)
Unmate force : 0.7 kgf (Min)
2.Terminal Retention : 0.5 kgf (Min)

Material :

1.Housing :
High Temperature Thermal Plastics,
UL 94V-0 , LCP , Black
2.Contact : PHOSPHOR BRONZE / BRASS
3.Shell : BRASS

Finish :

1.Contact : Plated Gold in Mating Area ;
Gold Plated on Solder Balls ;
Nickel under plated overall
2.Shell : Nickel under Plated surface layer

ITEM NO.	DESCRIPTION	DRAWN	DATE

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 11/04/13	MAT'L	
CHECKED BY: Jacky Chen	DATE 11/04/13	FINISH	
APPROVED BY: Tony Kao	DATE 11/04/13	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	CONNECTOR		
MODLE	MINI USB 5B/F 180 度 DIP 直插腳		
DWG NO.	MUSB-5B-VD-x-S175	SIZE	A4
PART NO.	MUSB-5B-VD-x-S175	VER	R