














Recommended PCB Layout

SPECIFICATIONS:

1.DISSIPATION CURRENT: 5.0 mA

2.PPERATING VOLTAGE(Vcc): 2.7-5.5 V

3.INSERTION FORCE:4.0Max Kgs

4.EXTRACTION FORCE:0.6Kgs TO 4.0 Kgs

5.ENDURANCE:500 CYCLES

6.OPERATING TEMPERATURE: -25 TO +70 ℃

OJ-G5006B-XX3-S214

TX

RX

ITEM	DESCRIPTIONs	MATERIAL	FINISH	Q'TY	NOTE
⑥	DRIVE IC(TX UNIT)			1	13 Mbps
⑤	COIL SPRING	SUS		1	
④	GATE	PBT		1	Black
③	FRAME	PBT		1	
②	COVER	PBT		1	
①	HOUSING	PBT		1	

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增傳輸代碼	Jack	112519
1	更新料號	Jack	070116

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 11/25/19	MAT'L	
CHECKED BY: Jacky Chen	DATE 11/25/19	FINISH	
APPROVED BY: Tony Kao	DATE 11/25/19	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	JACK		
MODLE	OPTICAL JACK		
DWG NO.	OJ-G5006B-XX3-S214	SIZE	A4
PART NO.	OJ-G5006B-XX3-S214	VER	R2