


MRUSB-5B-M17x-S347


SHELL鍍層:


TN
NI

















P.C.B LAYOUT MOUNTING PATTERN

NOTES:

MATERIAL:

1.1 HOUSING: LCP, UL94V-0 ,Black

1.2 CONTACT: PHOSPHOR BRONZE

1.3 SHELL: BRASS

FINISH:

2.1 CONTACT: PLATED GOLD IN MATING AREA ;
TIN PLATED ON SOLDER BALLS ;
NICKEL UNDER PLATED OVERALL

2.2 SHELL: NICKEL UNDER PLATED SURFACE LAYER OR
TIN UNDER PLATED SURFACE LAYER

3.SPECIFICATION:

3.1 RATING: 1.0A

3.2 DIELECTRIC WITHSSTANDING VOLTAGE: 100 VAC FOR 1 MIN

3.3 CONTACT RESISTANCE: 50 mΩ MAX.

3.4 INSULATION RESISTANCE: 100 MΩ MIN.

3.5 TOTAL MATING FORCE: 3.57 Kgf MAX.

3.6 TOTAL UNMATING FORCE: 1.0 Kgf MIN.

3.7 TEMPERATURE RANGE: -30°C ~ +80°C

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新底部樣式	Jack	080119
1	更新為A0版	Jack	010417

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S | UNITS MM

		DATE
DRAWN BY:	Jack Lu	08/01/19
CHECKED BY:	Jacky Chen	08/01/19
APPROVED BY:	Tony Kao	08/01/19

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	MICRO USB 2 腳沉板/板下1.6mm
SCALE	1 : 1	DWG NO.	MRUSB-5B-M17x-S347
SHEET NO.	1 of 1	PART NO.	MRUSB-5B-M17x-S347

SIZE A4 VER R2