



SPECIFICATION

1. Rating : DC 12V 1.0A
2. Contact resistance : $\leq 50m\Omega$
3. Insulation resistance : $\geq 100M\Omega$
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles
7. Waterproof Level: IPX7



NO.	DESCRIPTION	QTY	MATERIAL	PLATING
7	HOUSING	1	PA10T	
6	SHIELD	1	BRASS	Ni-Plating
5	5# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
4	4# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
3	3# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
2	2# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
1	1# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating

ITEM NO.	DESCRIPTION	DRAWN	DATE
4	更新材質表	Jack	082421
3	更新材質表	Jack	122520
2	更新材質	Jack	030717
1	新增SPEC	Jack	010816

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY: Jack Lu
 CHECKED BY: Jacky Chen
 APPROVED BY: Tony Kao

DATE: 08/24/21
 DATE: 08/24/21
 DATE: 08/24/21

MAT'L	TITLE	JACK
	JACK	
	MODLE	3.5mm PHONE JACK 防水型
SCALE 1 : 1	DWG NO.	PJ-WP30015DS
SHEET NO. 1 of 1	PART NO.	PJ-WP30015DS

SIZE A4
 VER R4