


P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATION

- 1.Rating : DC 30V 0.5A ;
- 2.Contact resistance : $\leq 0.03 \Omega$;
- 3.Insulation resistance : $\geq 100M \Omega$ (DC250V) ;
- 4.Withstand voltage : 500VAC ;
- 5.Insertion and extraction force : 3-30N;
- 6.life test : 5,000 cycles °

MODEL NO.	DC-011-x-S187
SCHEMATIC	
CENTER PIN	$\phi 1.0$ mm
	$\phi 1.3$ mm

1	FLAT FOOT	1	BRASS	Ag-Plating
2	SPRING PIECE	1	PHOSPHOR BRONZE	Ag-Plating
3	CURVE PIECE	1	BRASS	Ag-Plating
4	PIN	1	BRASS	Sn-Plating
5	HOUSING	1	PA	Black
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	09/18/13			
CHECKED BY:	DATE	FINISH	MODLE	DC JACK
Jacky Chen	09/18/13			
APPROVED BY:	DATE	SCALE	DWG NO.	DC-011-x-S187
Tony Kao	09/18/13	1 : 1		
		SHEET NO.	PART NO.	DC-011-x-S187
		1 of 1		
				SIZE A4
				VER R

ITEM NO.	DESCRIPTION	DRAWN	DATE